

Garant
Profile slotting toolholder for hexagon cutting inserts \varnothing D1 25 mm, from hexagon: 37 mm

Order data

| | |
|--------------|---------------|
| Order number | 290342 37 |
| GTIN | 4045197965646 |
| Item class | 21U |

Description
Note:

- **For machining centres, use the alignment aid No. 290397 and a dial indicator to check the spindle orientation.**
- **For lathes without Y-axis, please use eccentric bush No. 290391– 290393 for exact setting of the Y-coordinate.**

Through-coolant: yes

Shank length L_3 : 90 mm

suitable for hexagon drive: 37 - 45 mm

Reach L_1 : 126 mm

Tool holder \varnothing D_2 : 35 mm

Centre offset L_3 : 19.5 mm

Min. pre-drilling $-\varnothing$ D_{\min} : 37.2 mm

Screw: 290399 3

Technical description

| | |
|---|------------|
| Screw | 290399 3 |
| Reach L_1 | 126 mm |
| Min. pre-drilling $-\varnothing$ D_{\min} | 37.2 mm |
| Centre offset L_3 | 19.5 mm |
| suitable for hexagon drive | 37 - 45 mm |
| Shank \varnothing | 25 mm |

| | |
|-------------------------------|---|
| Tool holder $\varnothing D_2$ | 35 mm |
| Through-coolant | yes |
| Shank length L_s | 90 mm |
| Shank | Combination shank |
| Type of product | Keyway broaching and profile slotting tools |