

**Garant**
**Keyway broaching toolholder, long  $\varnothing$  DS 25 mm, from slot width m: 8 mm**

**Order data**

Order number	290350 8
GTIN	4045197880963
Item class	21U

**Description**
**Attention:**

Always use the minimum pre-drill  $\varnothing$  to match the slot width (e.g. for slot width 25 mm, minimum pre-drill  $\varnothing = 48$  mm).

**Note:**

- **Individual holder sizes are for different slot widths. In such cases, where possible, always use the optimum combination of holder and cutting insert (identical size) for maximum stability.**
- **For lathes without Y-axis, please use eccentric bush No. 290391– 290393 for exact setting of the Y-coordinate.**
- **For machining centres, use the alignment aid No. 290397 and a dial indicator to check the spindle orientation.**

suitable for slot width m: 8 mm

Reach  $L_1$ : 100 mm

Tool holder  $\varnothing D_1$ : 20 mm

Centre offset  $L_3$ : 11 mm

Min. pre-drilling  $-\varnothing D_{\min}$ : 22 mm

Screw: 290399 2

**Technical description**

suitable for slot width m	8 mm
Min. pre-drilling $-\varnothing D_{\min}$	22 mm
Reach $L_1$	100 mm
Screw	290399 2
Centre offset $L_3$	11 mm

Shank Ø	25 mm
Tool holder Ø D <sub>1</sub>	20 mm
Through-coolant	yes
Shank length L <sub>s</sub>	90 mm
Shank	Combination shank
Type of product	Keyway broaching and profile slotting tools

---

## Accessories

Fastening screw Type 3	290399 3
------------------------	----------