

Garant

Keyway broaching toolholder, long \varnothing DS 32 mm, from slot width m: 12 mm



Order data

Order number	290353 12
GTIN	4045197881052
Item class	21U

Description

Attention:

Always use the minimum pre-drill \varnothing to match the slot width (e.g. for slot width 25 mm, minimum pre-drill \varnothing = 48 mm).

Note:

- **Individual holder sizes are for different slot widths. In such cases, where possible, always use the optimum combination of holder and cutting insert (identical size) for maximum stability.**
- **For lathes without Y-axis, please use eccentric bush No. 290391– 290393 for exact setting of the Y-coordinate.**
- **For machining centres, use the alignment aid No. 290397 and a dial indicator to check the spindle orientation.**

suitable for slot width m: 12 mm

Reach L_1 : 161 mm

Tool holder \varnothing D_1 : 30 mm

Centre offset L_3 : 15.5 mm

Min. pre-drilling - \varnothing D_{min} : 33 mm

Screw: 290399 3

Technical description

Reach L_1	161 mm
Screw	290399 3
suitable for slot width m	12 mm
Min. pre-drilling - \varnothing D_{min}	33 mm
Centre offset L_3	15.5 mm

Shank \varnothing	32 mm
Tool holder $\varnothing D_1$	30 mm
Through-coolant	yes
Shank length L_s	100 mm
Shank	Combination shank
Type of product	Keyway broaching and profile slotting tools

Accessories

Fastening screw Type 3	290399 3
------------------------	----------