

**Cutting insert P9, TiN, for slot width m: 3 mm****Order data**

Order number	290360 3
GTIN	4045197881274
Item class	21U

**Description****Version:**

With TiN coating.

Suitable for regrinding.

**Application:**

For producing slots according to DIN 6885, DIN 138 and factory standards.

For slot widths with tolerance JS9, use cutter inserts with tolerance H7.

**Note:**

- **Special sizes (slot widths) available on request.**
- **From slot width 16 mm it is essential to perform two passes. The first pass must be performed for approx. half the slot width (e.g. 10 mm for a desired slot width of 18 mm).**
- **Application values can be found in the info block on page 773.**

**Note re advertising text:**

- **Special sizes (slot widths) available on request.**
- **From slot width 16 mm it is essential to perform two passes. The first pass must be performed for approx. half the slot width (e.g. 10 mm for a desired slot width of 18 mm).**
- **Application values can be found in the info block on page 724 in the catalogue Vol. 1.**

Chamfer: 0.2 mm×45°

Blade width w: 2.994 mm

Groove depth t: 1.42 mm

Tip thickness b: 6.5 mm

---

**Technical description**

Blade width w	2.994 mm
Groove depth t	1.42 mm
for slot width m	3 mm
Tip thickness b	6.5 mm
Tool material	HSS
Coating	TiN
for precision fit	P9
Chamfer	0.2 mm×45°
Type of product	Keyway broaching and profile slotting tools