

duMONT

Splined push broach HSS Fit JS9, Type: 6C1



Order data

Order number	290405 6C1
GTIN	662600444068
Item class	29J

Description

Application:

For production of keyways to DIN 6885.

Supplied with:

Broaches including the necessary shims.

Note:

- Broaches for high tensile materials, increased number of passes or special applications available (on request).
- After first and second of three passes, back the broach off slightly – the broach will then align itself.
- Coated broaches and inch size broaches available on request.
- BROACHING PRESSES can be found in Volume 2 (Hand tools and metrology).
- Size 28; 32 and 36 available on request, on short lead times.

Tool material: HSS

Broach length: 299 mm

Keyway width: 6 mm

Keyway depth: 2.8 mm

for bore Ø to DIN 6885: 18 - 22 mm

Broaching length in steel: 10 - 64 mm

necessary broaching force for St50 and max. broaching length: 1000 kg

Technical description

Back width	9.63 mm
Broaching length in steel	10 - 64 mm
necessary broaching force for St50 and max. broaching length	1000 kg
for bore Ø to DIN 6885	18 - 22 mm
Keyway depth	2.8 mm
Keyway width	6 mm
Broach length	299 mm
Number of passes	2
Tool material	HSS
Type of product	Broach

Accessories

Shim for push broach No. 290405 – 407 Type 6C1	290410 6C1
--	------------