



## Smooth rolling tool EG5 universal, Shank mounting type: VDI30



### Order data

Order number	291505 VDI30
GTIN	4060491000077
Item class	29F

### Description

#### Version:

For use on CNC and conventional lathes.

With symmetrical structure – can be used universally as right-hand or left-hand version.

#### Advantage:

Surface quality  $R_z < 1.0 \mu\text{m}$  possible.

Feed rates up to 1.0 mm/rev possible (external machining).

Consistent results due to continuous measurement of the rolling force.

#### Application:

For mechanical surface finishing.

For machining all metallic materials up to a tensile strength of  $1400 \text{ N/mm}^2$  and a hardness of up to 45 HRC.

#### Suitable for :

Ø range (recommended): 10 – 100 mm

#### Supplied with:

Two spare rolls built in the cage.

#### Note:

Tool tray for the respective machining surface depends on the type of turret (star/disc).

· **Other shank connections on request.**

· **Detailed technology recommendations can be found in the instruction manual.**

Cutting direction: Left-hand and right-hand

Overhang  $L_1$ : 121 mm

Tip centre offset f: 80 mm

maximum rolling force: 3 kN

Roll Ø: 5 mm

## Technical description

Tip centre offset f	80 mm
Roll Ø	5 mm
maximum rolling force	3 kN
Overhang L <sub>1</sub>	121 mm
Shank mounting type	VDI30
Cutting direction	Left-hand and right-hand
Type of product	Smooth rolling tool