



Smooth rolling tool G, Parallel shank \varnothing 20 mm, \varnothing D: 24 mm



Order data

Order number	291553 24
GTIN	4060491000480
Item class	29F

Description

Version:

For use on CNC and conventional lathes, milling and drilling machines.
Stepless adjustment in μm (adjustment range from -0.05 to $+0.1$ mm).

Advantage:

Specially for production use. Maximum productivity due to **feeds** from $0.05 - 0.3$ mm **per roll**.

Surface quality up to $R_z < 1.0$ μm possible.

Automatic release during tool withdrawal avoids damage to smooth rolled surface.

Application:

- **For mechanical surface finishing.**
- **For machining all metallic materials up to a tensile strength of 1400 N/mm^2 and a hardness of up to 45 HRC.**
- **Clockwise machining.**
- **Up to tolerance class IT8.**
- **For holes up to $\varnothing 49$ mm.**

Note:

From $\varnothing 10$ mm optionally with internal cooling.

Application for type of drilling: for blind hole and through hole

Overhang L_1 : 128 mm

Reach L_1 : 50 mm

Adjustment range: $-0.05 / +0.1$ mm

Shank $\varnothing D_s$: 35 mm

Number of rolls: 5

Technical description

Shank $\varnothing D_s$	35 mm
-------------------------	-------

Number of rolls	5
Overhang L ₁	128 mm
Adjustment range	-0.05 / +0.1 mm
Nominal Ø D	24 mm
Reach L ₁	50 mm
Shank mounting type	Parallel shank Ø 20 mm
Application for type of drilling	for blind hole and through hole
Type of product	Smooth rolling tool