



## Smooth rolling tool G, Parallel shank $\varnothing$ 25 mm, $\varnothing$ D: 47 mm



### Order data

Order number	291556 47
GTIN	4060491000701
Item class	29F

### Description

#### Version:

For use on CNC and conventional lathes, milling and drilling machines.  
Stepless adjustment in  $\mu\text{m}$  (adjustment range from -0.05 to +0.1 mm).

#### Advantage:

**Specially for production use.** Maximum productivity due to **feeds** from 0.05 - 0.3 mm **per roll**.  
Surface quality up to  $R_z < 1.0 \mu\text{m}$  possible.  
Automatic release during tool withdrawal avoids damage to smooth rolled surface.

#### Application:

- **For mechanical surface finishing.**
- **For machining all metallic materials up to a tensile strength of  $1400 \text{ N/mm}^2$  and a hardness of up to 45 HRC.**
- **Clockwise machining.**
- **Up to tolerance class IT8.**
- **For holes up to  $\varnothing$  49 mm.**

#### Note:

From  $\varnothing$  10 mm optionally with internal cooling.  
Application for type of drilling: for blind hole and through hole  
Overhang  $L_1$ : 163 mm  
Reach  $L_1$ : 162 mm  
Adjustment range: -0.05 / +0.1 mm  
Shank  $\varnothing$   $D_s$ : 35 mm  
Number of rolls: 8

### Technical description

Reach $L_1$	162 mm
-------------	--------

Nominal $\varnothing$ D	47 mm
Adjustment range	-0.05 / +0.1 mm
Number of rolls	8
Shank $\varnothing$ D <sub>s</sub>	35 mm
Overhang L <sub>1</sub>	163 mm
Shank mounting type	Parallel shank $\varnothing$ 25 mm
Application for type of drilling	for blind hole and through hole
Type of product	Smooth rolling tool