



## Smooth rolling tool G, MK2, Ø D: 17 mm



### Order data

Order number	291559 17
GTIN	4060491000848
Item class	29F

### Description

#### Version:

For use on CNC and conventional lathes, milling and drilling machines.  
Stepless adjustment in  $\mu\text{m}$  (adjustment range from  $-0.05$  to  $+0.1$  mm).

#### Advantage:

**Specially for production use.** Maximum productivity due to **feeds** from  $0.05$  -  $0.3$  mm **per roll**.  
Surface quality up to  $R_z < 1.0$   $\mu\text{m}$  possible.  
Automatic release during tool withdrawal avoids damage to smooth rolled surface.

#### Application:

- **For mechanical surface finishing.**
- **For machining all metallic materials up to a tensile strength of  $1400$  N/mm<sup>2</sup> and a hardness of up to 45 HRC.**
- **Clockwise machining.**
- **Up to tolerance class IT8.**
- **For holes up to  $\varnothing 49$  mm.**

#### Note:

From  $\varnothing 10$  mm optionally with internal cooling.  
Application for type of drilling: for blind hole and through hole  
Overhang  $L_1$ : 128 mm  
Reach  $L_1$ : 50 mm  
Adjustment range:  $-0.05$  /  $+0.1$  mm  
Shank  $\varnothing D_s$ : 35 mm  
Number of rolls: 5

### Technical description

Adjustment range	$-0.05$ / $+0.1$ mm
------------------	---------------------

Shank $\varnothing D_s$	35 mm
Overhang $L_1$	128 mm
Reach $L_1$	50 mm
Nominal $\varnothing D$	17 mm
Number of rolls	5
Shank mounting type	MK2
Application for type of drilling	for blind hole and through hole
Type of product	Smooth rolling tool