



Smooth rolling tool G, MK2, Ø D: 19 mm



Order data

Order number	291559 19
GTIN	4060491000862
Item class	29F

Description

Version:

For use on CNC and conventional lathes, milling and drilling machines.
Stepless adjustment in μm (adjustment range from -0.05 to +0.1 mm).

Advantage:

Specially for production use. Maximum productivity due to **feeds** from 0.05 - 0.3 mm **per roll**.
Surface quality up to $R_z < 1.0 \mu\text{m}$ possible.
Automatic release during tool withdrawal avoids damage to smooth rolled surface.

Application:

- **For mechanical surface finishing.**
- **For machining all metallic materials up to a tensile strength of 1400 N/mm² and a hardness of up to 45 HRC.**
- **Clockwise machining.**
- **Up to tolerance class IT8.**
- **For holes up to Ø 49 mm.**

Note:

From Ø 10 mm optionally with internal cooling.
Application for type of drilling: for blind hole and through hole
Overhang L_1 : 128 mm
Reach L_1 : 50 mm
Adjustment range: -0.05 / +0.1 mm
Shank Ø D_s : 35 mm
Number of rolls: 5

Technical description

Shank Ø D_s	35 mm
---------------	-------

Reach L ₁	50 mm
Nominal Ø D	19 mm
Overhang L ₁	128 mm
Number of rolls	5
Adjustment range	-0.05 / +0.1 mm
Shank mounting type	MK2
Application for type of drilling	for blind hole and through hole
Type of product	Smooth rolling tool