



Smooth rolling tool G, MK3, Ø D: 40 mm



Order data

Order number	291562 40
GTIN	4060491001036
Item class	29F

Description

Version:

For use on CNC and conventional lathes, milling and drilling machines.
Stepless adjustment in μm (adjustment range from -0.05 to $+0.1$ mm).

Advantage:

Specially for production use. Maximum productivity due to **feeds** from $0.05 - 0.3$ mm **per roll**.

Surface quality up to $R_z < 1.0$ μm possible.

Automatic release during tool withdrawal avoids damage to smooth rolled surface.

Application:

- **For mechanical surface finishing.**
- **For machining all metallic materials up to a tensile strength of 1400 N/mm² and a hardness of up to 45 HRC.**
- **Clockwise machining.**
- **Up to tolerance class IT8.**
- **For holes up to $\varnothing 49$ mm.**

Note:

From $\varnothing 10$ mm optionally with internal cooling.

Application for type of drilling: for blind hole and through hole

Overhang L_1 : 163 mm

Reach L_1 : 162 mm

Adjustment range: $-0.05 / +0.1$ mm

Shank $\varnothing D_s$: 35 mm

Number of rolls: 8

Technical description

Reach L_1	162 mm
-------------	--------

Adjustment range	-0.05 / +0.1 mm
Nominal \varnothing D	40 mm
Overhang L ₁	163 mm
Number of rolls	8
Shank \varnothing D _s	35 mm
Shank mounting type	MK3
Application for type of drilling	for blind hole and through hole
Type of product	Smooth rolling tool