

Garant

Profile broaching insert, square socket metric $\varnothing d = 16$ mm, Square: 5 mm


Order data

| | |
|--------------|---------------|
| Order number | 293056 5 |
| GTIN | 4045197947123 |
| Item class | 29L |

Description
Version:

With TiN coating.

Application:

For generation of profiles **in a single pass**.

Suitable for :

Profile broaching holder No. 293020 – 293079.

Note:

- **Special sizes and special profiles available in request.**
- **Detailed application values can be found in the info block on page 806.**

The manufacture of square profiles > 9 mm is recommended only in easily machined materials (higher rate of material removal).

Note re advertising text:

- **Special sizes and special profiles available on request.**
- **Detailed application values can be found in the info block on page 727 in the catalogue Vol. 1.**

L_1 : 40 mm

L: 8.5 mm

Tolerance: + 0.12 to + 0.15 mm

Technical description

| | |
|--------------------|---------------------------------------------|
| L | 8.5 mm |
| Width across flats | 5 mm |
| Tool material | HSS |
| Tolerance | + 0.12 to + 0.15 mm |
| Profile | Square |
| L ₁ | 40 mm |
| Ø d | 16 mm |
| Coating | TiN |
| Type of product | Keyway broaching and profile slotting tools |