

Garant
Side lock arbor Form ADB, SK 40 A = 100, Clamping range \varnothing D1: 16 mm

Order data

Order number	300230 16
GTIN	4045197282958
Item class	31A

Description
Version:

With Balluffchip bore.

GARANT –

All shanks hard turned (for smooth cutting action!). Balancing quality G 2.5 / G 25,000 rpm

Application:

For clamping tools with side flat to DIN 1835 B and DIN 6535 HB.

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

External \varnothing D: 48 mm

Spare clamping screw No. 30 9900: 16

Technical description

Spare clamping screw No. 30 9900	16
Clamping \varnothing D ₁	16 mm
External \varnothing D	48 mm
Adapter	SK 40 A = 100
Standard	DIN 6359
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm

Concentricity	≤ 3 µm
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud sealed, form B suitable for steep tapers 40	308650 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Pull stud Form B suitable for steep tapers 40	308640 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
	308670 40M

Pull stud Mazak sealed, form A suitable for steep tapers
40M

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers
40

308630 40

Torque insert for Pull studs to SO 7388 suitable for ISO
taper size 40

308812 40

Pull stud Form A suitable for steep tapers 40

308600 40

Pull stud sealed suitable for steep tapers 40

308635 40

Pull stud Hurco 90° with fit sealed suitable for steep tapers
40

308806 40

Special pull stud with internal thread suitable for steep
tapers 40

308740 40

Pull stud 90° sealed suitable for steep tapers 40

308795 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers
40

308625 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers
40

308802 40

Spare clamping screw for chucks with clamping \varnothing D1 16
mm

309900 16