

**Garant**
**Side lock arbor Form ADB with cooling channel bores, SK 40 A = 130,  
Clamping range  $\varnothing D_1$ : 6 mm**

**Order data**

Order number	300271 6
GTIN	4045197645906
Item class	31A

**Description**
**Version:**

With Balluffchip bore.

**GARANT –**

All shanks hard turned (for smooth cutting action!). Balancing quality G 2.5 / G 25,000 rpm

**With coolant supply holes that can be plugged.**

**Application:**

For clamping tools with side flat to DIN 1835 B and DIN 6535 HB.

**Optional extras:**

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

External  $\varnothing D$ : 25 mm

Spare clamping screw No. 30 9900: 6

**Technical description**

Clamping $\varnothing D_1$	6 mm
Spare clamping screw No. 30 9900	6
External $\varnothing D$	25 mm
Adapter	SK 40 A = 130
Standard	DIN 6359
Arbor standard	ISO 7388-1
Shape	ADB

Cooling channel bore	pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HPC
Type of product	Side lock arbor

## Accessories

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud Form B suitable for steep tapers 40	308640 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
Pull stud Form A suitable for steep tapers 40	308600 40
Pull stud sealed, form B suitable for steep tapers 40	308650 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
	308720 40

Special pull stud with no internal thread sealed suitable for steep tapers 40

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40

308820 40

Pull stud stud sealed, form A suitable for steep tapers 40

308610 40

Pull stud 45° sealed suitable for steep tapers 40

308765 40

Pull stud sealed, form B suitable for steep tapers 40

308620 40

Pull stud sealed suitable for steep tapers 40

308635 40

Special pull stud with no internal thread sealed suitable for steep tapers 40

308700 40

Pull stud 90° sealed suitable for steep tapers 40

308790 40

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40

308605 40

Special pull stud with internal thread suitable for steep tapers 40

308740 40

Pull stud 45° sealed suitable for steep tapers 40

308760 40

Pull stud 60° sealed suitable for steep tapers 40

308785 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40

308802 40

Spare clamping screw for chucks with clamping Ø D1 6 mm

309900 6