

Garant

**Side lock arbor Form ADB with cooling channel bores, SK 40 A = 160,
Clamping range \varnothing D1: 10 mm**


Order data

Order number	300276 10
GTIN	4045197829856
Item class	31A

Description
Version:

With coolant supply holes that can be plugged.

GARANT –

All shanks hard turned (for smooth cutting action!). Balancing quality G 2.5 / G 25,000 rpm
With Balluffchip bore.

Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Machining strategy: HPC

External \varnothing D: 35 mm

Spare clamping screw No. 30 9900: 10

Technical description

Clamping \varnothing D ₁	10 mm
Spare clamping screw No. 30 9900	10
External \varnothing D	35 mm
Adapter	SK 40 A = 160
Standard	DIN 6359
Arbor standard	ISO 7388-1

Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull stud Form B suitable for steep tapers 40	308640 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Pull stud Form A suitable for steep tapers 40	308600 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Pull stud sealed suitable for steep tapers 40	308635 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
	308801 40

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40

Pull stud 60° sealed suitable for steep tapers 40

308785 40

Pull stud 90° sealed suitable for steep tapers 40

308795 40

Pull stud sealed, form B suitable for steep tapers 40

308650 40

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40

308806 40

Pull stud sealed, form B suitable for steep tapers 40

308620 40

Special pull stud with no internal thread sealed suitable for steep tapers 40

308700 40

Special pull stud with no internal thread sealed suitable for steep tapers 40

308720 40

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40

308615 40

Pull stud Mazak sealed, form A suitable for steep tapers 40M

308670 40M

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40

308630 40

Pull stud sealed suitable for steep tapers 40

308660 40

Spare clamping screw for chucks with clamping \varnothing D1 10 mm

309900 10