

**Garant**

**Side lock arbor Form ADB with cooling channel bores, SK 40 A = 160,  
Clamping range  $\varnothing D_1$ : 8 mm**


**Order data**

|              |               |
|--------------|---------------|
| Order number | 300276 8      |
| GTIN         | 4045197829849 |
| Item class   | 31A           |

**Description**
**Version:**

**With coolant supply holes that can be plugged.**

**GARANT –**

All shanks hard turned (for smooth cutting action!). Balancing quality G 2.5 / G 25,000 rpm  
With Balluffchip bore.

**Application:**

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

**Optional extras:**

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Machining strategy: HPC

External  $\varnothing D$ : 28 mm

Spare clamping screw No. 30 9900: 8

**Technical description**

|                                  |               |
|----------------------------------|---------------|
| Spare clamping screw No. 30 9900 | 8             |
| Clamping $\varnothing D_1$       | 8 mm          |
| External $\varnothing D$         | 28 mm         |
| Adapter                          | SK 40 A = 160 |
| Standard                         | DIN 6359      |
| Arbor standard                   | ISO 7388-1    |

|                                       |                     |
|---------------------------------------|---------------------|
| Shape                                 | ADB                 |
| Balance quality G at rotational speed | G 2.5 at 25,000 rpm |
| Concentricity                         | ≤ 3 μm              |
| Machining strategy                    | HPC                 |
| Type of product                       | Side lock arbor     |

## Accessories

|   |           |
|---|-----------|
| Pull stud sealed suitable for steep tapers 40                                 | 308635 40 |
| Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40     | 308801 40 |
| Pull stud sealed, form B suitable for steep tapers 40                         | 308620 40 |
| Wrench for pull studs ISO 7388 suitable for ISO taper size 40                 | 308830 40 |
| Pull stud 45° sealed suitable for steep tapers 40                             | 308765 40 |
| Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40              | 308615 40 |
| Pull stud Hurco 45° with fit sealed suitable for steep tapers 40              | 308802 40 |
| Special pull stud with no internal thread sealed suitable for steep tapers 40 | 308700 40 |
| Pull stud 90° sealed suitable for steep tapers 40                             | 308795 40 |
| Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40             | 308625 40 |
| Pull stud sealed, form B suitable for steep tapers 40                         | 308650 40 |
| Special pull stud with internal thread suitable for steep tapers 40           | 308740 40 |
| Pull stud 90° sealed suitable for steep tapers 40                             | 308790 40 |
| Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40                      | 308605 40 |
| Pull stud sealed suitable for steep tapers 40                                 | 308660 40 |
|   | 308812 40 |

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40

|  |            |
|--|------------|
| Pull stud Form B suitable for steep tapers 40  | 308640 40  |
| Pull stud stud sealed, form A suitable for steep tapers 40                               | 308610 40  |
| Special pull stud with no internal thread sealed suitable for steep tapers 40            | 308720 40  |
| Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40 | 308820 40  |
| Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40                        | 308630 40  |
| Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40                 | 308810 40  |
| Pull stud Mazak sealed, form A suitable for steep tapers 40M                             | 308670 40M |
| Pull stud Form A suitable for steep tapers 40  | 308600 40  |
| Pull stud 45° sealed suitable for steep tapers 40  | 308760 40  |
| Pull stud 60° sealed suitable for steep tapers 40  | 308785 40  |
| Pull stud Hurco 90° with fit sealed suitable for steep tapers 40                         | 308806 40  |
| Spare clamping screw for chucks with clamping Ø D1 8 mm                                  | 309900 8   |