

**Garant**
**Side lock arbor Form ADB, SK 40 A = 200, Clamping range Ø D1: 20 mm**

**Order data**

Order number	300285 20
GTIN	4045197283252
Item class	31A

**Description**
**Version:**

With Balluffchip bore.

**GARANT –**

All shanks hard turned (for smooth cutting action!). Balancing quality G 2.5 / G 25,000 rpm

**Application:**

For clamping tools with side flat to DIN 1835 B and DIN 6535 HB.

**Optional extras:**

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

External Ø D: 52 mm

Spare clamping screw No. 30 9900: 20

**Technical description**

Spare clamping screw No. 30 9900	20
Clamping Ø D <sub>1</sub>	20 mm
External Ø D	52 mm
Adapter	SK 40 A = 200
Standard	DIN 6359
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm

Machining strategy	HPC
Type of product	Side lock arbor

## Accessories

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Pull stud sealed suitable for steep tapers 40	308635 40
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud Form B suitable for steep tapers 40	308640 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
	308625 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40

308615 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40

308802 40

Pull stud 45° sealed suitable for steep tapers 40

308765 40

Pull stud 60° sealed suitable for steep tapers 40

308785 40

Pull stud sealed, form B suitable for steep tapers 40

308650 40

Pull stud Mazak sealed, form A suitable for steep tapers 40M

308670 40M

Pull stud Form A suitable for steep tapers 40

308600 40

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40

308812 40

Pull stud 90° sealed suitable for steep tapers 40

308795 40

Spare clamping screw for chucks with clamping  $\varnothing$  D1 20 mm

309900 20