

Garant
Side lock arbor Form AD, SK 40 ultra short, Clamping range \varnothing D1: 20 mm

Order data

Order number	300410 20
GTIN	4045197284358
Item class	31A

Description
Version:

Locking screw in tool gripper groove.

Application:

For clamping tools with side flat to DIN 1835 B and DIN 6535 HB.

Standard:

Ähnlich DIN 69871.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820; 308830, spare screw No. 309901.

Concentricity: $\leq 3 \mu\text{m}$

Overhang dimension A: 40 mm

External \varnothing D: 50 mm

Technical description

Clamping \varnothing D ₁	20 mm
Overhang dimension A	40 mm
External \varnothing D	50 mm
Adapter	SK 40 ultra short
Standard	DIN 6359
Arbor standard	ISO 7388-1

Shape	AD
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Type of product	Side lock arbor

Accessories

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud sealed suitable for steep tapers 40	308635 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud Form A suitable for steep tapers 40	308600 40
Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
	308801 40

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40

Pull stud sealed, form B suitable for steep tapers 40 308650 40

Pull-stud 60° sealed suitable for steep tapers 40 308780 40

Special pull stud with no internal thread sealed suitable for steep tapers 40 308700 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40 308802 40

Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40 308805 40

Pull stud sealed, form B suitable for steep tapers 40 308620 40

Pull stud 90° sealed suitable for steep tapers 40 308795 40

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40 308806 40

Wrench for pull studs ISO 7388 suitable for ISO taper size 40 308830 40

Pull stud 90° sealed suitable for steep tapers 40 308790 40

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40 308605 40

Pull stud sealed suitable for steep tapers 40 308660 40

Pull stud Form B suitable for steep tapers 40 308640 40

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40 308812 40

Clamping screw for Weldon arbor ultra short for chuck clamping Ø D1 20 mm 309901 20

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40 308615 40