

**Garant**
**Side lock arbor Form AD, SK 40 ultra short, Clamping range  $\varnothing$  D1: 25 mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 300410 25     |
| GTIN         | 4045197284365 |
| Item class   | 31A           |

**Description**
**Version:**

With only a single shorter locking screw.

**Application:**

For clamping tools with side flat to DIN 1835 B and DIN 6535 HB.

**Standard:**

Ähnlich DIN 69871.

**Optional extras:**

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820; 308830, spare screw No. 309901.

Concentricity:  $\leq 3 \mu\text{m}$

Overhang dimension A: 60 mm

External  $\varnothing$  D: 65 mm

**Technical description**

|                                       |                   |
|---------------------------------------|-------------------|
| Overhang dimension A                  | 60 mm             |
| Clamping $\varnothing$ D <sub>1</sub> | 25 mm             |
| External $\varnothing$ D              | 65 mm             |
| Adapter                               | SK 40 ultra short |
| Standard                              | DIN 6359          |
| Arbor standard                        | ISO 7388-1        |
| Shape                                 | AD                |

|                                       |                     |
|---------------------------------------|---------------------|
| Balance quality G at rotational speed | G 2.5 at 25,000 rpm |
| Concentricity                         | ≤ 3 μm              |
| Type of product                       | Side lock arbor     |

## Accessories

|   |            |
|---|------------|
| Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40      | 308810 40  |
| Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40     | 308805 40  |
| Pull stud sealed, form B suitable for steep tapers 40                         | 308620 40  |
| Pull stud Hurco 45° with fit sealed suitable for steep tapers 40              | 308802 40  |
| Pull stud sealed suitable for steep tapers 40                                 | 308635 40  |
| Pull stud Mazak sealed, form A suitable for steep tapers 40M                  | 308670 40M |
| Pull stud Hurco 90° with fit sealed suitable for steep tapers 40              | 308806 40  |
| Special pull stud with no internal thread sealed suitable for steep tapers 40 | 308720 40  |
| Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40     | 308803 40  |
| Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40             | 308625 40  |
| Pull stud sealed, form B suitable for steep tapers 40                         | 308650 40  |
| Clamping screw for Weldon arbor ultra short for chuck clamping Ø D1 25 mm     | 309901 25  |
| Special pull stud with no internal thread sealed suitable for steep tapers 40 | 308700 40  |
| Pull stud 90° sealed suitable for steep tapers 40                             | 308790 40  |
| Pull stud Form B suitable for steep tapers 40                                 | 308640 40  |
| Pull stud Form A suitable for steep tapers 40                                 | 308600 40  |

|  |           |
|--|-----------|
| Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40                   | 308812 40 |
| Pull stud Hurco 60° with fit sealed suitable for steep tapers 40                         | 308804 40 |
| Pull stud 45° sealed suitable for steep tapers 40  | 308760 40 |
| Pull stud sealed suitable for steep tapers 40  | 308660 40 |
| Wrench for pull studs ISO 7388 suitable for ISO taper size 40                            | 308830 40 |
| Pull stud 90° sealed suitable for steep tapers 40  | 308795 40 |
| Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40                                 | 308605 40 |
| Special pull stud with internal thread suitable for steep tapers 40                      | 308740 40 |
| Pull stud stud sealed, form A suitable for steep tapers 40                               | 308610 40 |
| Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40                         | 308615 40 |
| Pull stud 60° sealed suitable for steep tapers 40  | 308785 40 |
| Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40 | 308820 40 |
| Pull-stud 60° sealed suitable for steep tapers 40  | 308780 40 |
| Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40                        | 308630 40 |
| Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40                | 308801 40 |
| Pull stud 45° sealed suitable for steep tapers 40  | 308765 40 |