

Garant
Holder for Weldon shanks, cylindrical, slim, Clamping range Ø D1: 16 mm

Order data

Order number	300415 16
GTIN	4045197701831
Item class	31A

Description
Version:

Cylindrical holder with Weldon shank and two clamping screws for clamping the tool. Ø 6 mm through hole for **internal cooling** provided.

Version:

Type of clamping screw: M14 × 1 – SKT 5

Advantage:

Low interference contour due to slim design and variation of the clamped lengths.

Application:

For clamping tools with side flat to DIN 1835 B and DIN 6535 HB.

Supplied with:

Including insert screw No. 300416.

Through-coolant: yes

External Ø D: 25 mm

L₁: 100 mm

Ø D₂: 26 mm

Overall length L: 156 mm

Technical description

Overall length L	156 mm
Clamping Ø D ₁	16 mm
L ₁	100 mm
Ø D ₂	26 mm
External Ø D	25 mm
Through-coolant	yes

Type of product	Side lock arbor
-----------------	-----------------

Accessories

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
--	-----------

Pull stud sealed suitable for steep tapers 40	308660 40
---	-----------

Pull stud sealed, form B suitable for steep tapers 40	308620 40
---	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 50	308700 50
---	-----------

Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
--	-----------

Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50
---	-----------

Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
--	-----------

Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
---	-----------

Pull stud 45° sealed suitable for steep tapers 50	308760 50
---	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
---	-----------

Pull stud sealed, form B suitable for steep tapers 40	308650 40
---	-----------

Pull stud 90° sealed suitable for steep tapers 50	308790 50
---	-----------

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50	308605 50
--	-----------

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
--	-----------

Pull stud 45° sealed suitable for steep tapers 30	308760 30
---	-----------

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
---	-----------

Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
--	-----------

Pull stud Form B suitable for steep tapers 40	308640 40
---	-----------

	308802 40
--	-----------

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40

Pull stud Form B suitable for steep tapers 50 308640 50

Pull stud 90° sealed suitable for steep tapers 40 308795 40

Special pull stud with no internal thread sealed suitable for steep tapers 40 308700 40

Special pull stud with internal thread suitable for steep tapers 50 308740 50

Clamping screw for micro-clamp arbor Thread size M14 300416 M14

Pull stud 45° sealed suitable for steep tapers 40 308765 40

Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40 308805 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40 308630 40

Pull stud stud sealed, form A suitable for steep tapers 50 308610 50

Pull stud stud sealed, form A suitable for steep tapers 40 308610 40

Pull stud 45° sealed suitable for steep tapers 40 308760 40

Pull stud Mazak sealed, form A suitable for steep tapers 40M 308670 40M

Pull stud sealed suitable for steep tapers 50 308660 50

Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40 308803 40

Pull-stud 60° sealed suitable for steep tapers 50 308780 50

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50 308820 50

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50 308812 50

Pull-stud 60° sealed suitable for steep tapers 40 308780 40

Pull stud 45° sealed suitable for steep tapers 50 308765 50

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40 308615 40

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40 308806 40

Special pull stud with internal thread suitable for steep tapers 40	308740 40
Pull stud sealed, form B suitable for steep tapers 50	308620 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Pull stud sealed, form A suitable for steep tapers 30	308610 30
Pull stud sealed suitable for steep tapers 40	308635 40
Pull stud sealed, form B suitable for steep tapers 50	308650 50
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
Pull-stud 60° sealed suitable for steep tapers 30	308780 30
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull stud Form A suitable for steep tapers 40	308600 40
Pull stud Form A suitable for steep tapers 50	308600 50
Pull stud 45° sealed suitable for steep tapers 30	308765 30
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Pull stud 60° sealed suitable for steep tapers 30	308785 30