

Garant
Holder for Weldon shanks, cylindrical, slim, Clamping range Ø D1: 18 mm

Order data

Order number	300415 18
GTIN	4045197701848
Item class	31A

Description
Version:

Cylindrical holder with Weldon shank and two clamping screws for clamping the tool. Ø 6 mm through hole for **internal cooling** provided.

Version:

Type of clamping screw: M14 × 1 – SKT 5

Advantage:

Low interference contour due to slim design and variation of the clamped lengths.

Application:

For clamping tools with side flat to DIN 1835 B and DIN 6535 HB.

Supplied with:

Including insert screw No. 300416.

Through-coolant: yes

External Ø D: 25 mm

L₁: 100 mm

Ø D₂: 28 mm

Overall length L: 156 mm

Technical description

Overall length L	156 mm
Ø D ₂	28 mm
Clamping Ø D ₁	18 mm
L ₁	100 mm
External Ø D	25 mm
Through-coolant	yes

Type of product	Side lock arbor
-----------------	-----------------

Accessories

Pull stud sealed, form B suitable for steep tapers 40	308650 40
---	-----------

Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
---	-----------

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
---	-----------

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
--	-----------

Pull stud 90° sealed suitable for steep tapers 40	308795 40
---	-----------

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
---	-----------

Pull stud stud sealed, form A suitable for steep tapers 30	308610 30
--	-----------

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50	308820 50
--	-----------

Pull stud 90° sealed suitable for steep tapers 50	308790 50
---	-----------

Pull stud sealed, form B suitable for steep tapers 40	308620 40
---	-----------

Pull-stud 60° sealed suitable for steep tapers 40	308780 40
---	-----------

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
---	-----------

Pull stud Form B suitable for steep tapers 40	308640 40
---	-----------

Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
--	------------

Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
---	-----------

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
--	-----------

Pull stud sealed, form B suitable for steep tapers 50	308650 50
---	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
---	-----------

Pull stud stud sealed, form A suitable for steep tapers 50	308610 50
Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud 45° sealed suitable for steep tapers 50	308760 50
Pull stud 45° sealed suitable for steep tapers 30	308760 30
Pull stud sealed, form B suitable for steep tapers 50	308620 50
Pull stud Form A suitable for steep tapers 50	308600 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Pull stud 60° sealed suitable for steep tapers 30	308785 30
Pull stud Form B suitable for steep tapers 50	308640 50
Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50	308812 50
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50	308605 50
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Pull-stud 60° sealed suitable for steep tapers 30	308780 30
Pull stud 45° sealed suitable for steep tapers 50	308765 50
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
	308802 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40

Pull stud sealed suitable for steep tapers 40	308635 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud sealed suitable for steep tapers 50	308660 50
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud Form A suitable for steep tapers 40	308600 40
Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
Clamping screw for micro-clamp arbor Thread size M14	300416 M14
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull-stud 60° sealed suitable for steep tapers 50	308780 50
Special pull stud with internal thread suitable for steep tapers 50	308740 50
Pull stud 45° sealed suitable for steep tapers 30	308765 30
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Special pull stud with no internal thread sealed suitable for steep tapers 50	308700 50
Special pull stud with internal thread suitable for steep tapers 40	308740 40