

Garant
Holder for Weldon shanks, cylindrical, slim, Clamping range \varnothing D1: 6 mm

Order data

Order number	300415 6
GTIN	4045197700889
Item class	31A

Description
Version:

Cylindrical holder with Weldon shank and two clamping screws for clamping the tool. \varnothing 6 mm through hole for **internal cooling** provided.

Version:

Type of clamping screw: M6 \times 0.5 – TX 10

Advantage:

Low interference contour due to slim design and variation of the clamped lengths.

Application:

For clamping tools with side flat to DIN 1835 B and DIN 6535 HB.

Supplied with:

Including insert screw No. 300416.

Through-coolant: yes

External \varnothing D: 20 mm

L₁: 40 mm

\varnothing D₂: 9.8 mm

Overall length L: 150 mm

Technical description

Clamping \varnothing D ₁	6 mm
L ₁	40 mm
Overall length L	150 mm
\varnothing D ₂	9.8 mm
External \varnothing D	20 mm
Through-coolant	yes

Type of product	Side lock arbor
-----------------	-----------------

Accessories

Pull stud 60° sealed suitable for steep tapers 40	308785 40
---	-----------

Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
---	-----------

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
---	-----------

Clamping screw for micro-clamp arbor Thread size M6	300416 M6
---	-----------

Pull stud 45° sealed suitable for steep tapers 50	308765 50
---	-----------

Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50
---	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
---	-----------

Pull stud sealed suitable for steep tapers 50	308660 50
---	-----------

Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
---	-----------

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
--	-----------

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
--	-----------

Pull stud Form A suitable for steep tapers 40	308600 40
---	-----------

Pull stud sealed, form B suitable for steep tapers 40	308620 40
---	-----------

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
--	-----------

Pull stud 60° sealed suitable for steep tapers 50	308785 50
---	-----------

Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
--	-----------

Pull stud 90° sealed suitable for steep tapers 40	308790 40
---	-----------

Pull stud sealed, form B suitable for steep tapers 40	308650 40
---	-----------

Pull-stud 60° sealed suitable for steep tapers 50	308780 50
---	-----------

	308802 40
--	-----------

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40

Pull-stud 60° sealed suitable for steep tapers 30	308780 30
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50	308820 50
Pull stud sealed suitable for steep tapers 40	308635 40
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Pull stud 45° sealed suitable for steep tapers 30	308760 30
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
Pull stud stud sealed, form A suitable for steep tapers 30	308610 30
Pull stud stud sealed, form A suitable for steep tapers 50	308610 50
Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
Pull stud sealed, form B suitable for steep tapers 50	308650 50
Pull stud 45° sealed suitable for steep tapers 50	308760 50
	308810 40

Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40

Special pull stud with internal thread suitable for steep tapers 50

308740 50

Pull stud sealed, form B suitable for steep tapers 50

308620 50

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50

308812 50

Pull stud Form B suitable for steep tapers 50

308640 50

Pull stud Hurco 60° with fit sealed suitable for steep tapers 40

308804 40

Pull stud 60° sealed suitable for steep tapers 30

308785 30

Pull stud 45° sealed suitable for steep tapers 40

308765 40

Pull stud Form A suitable for steep tapers 50

308600 50

Special pull stud with no internal thread sealed suitable for steep tapers 50

308700 50

Pull stud 45° sealed suitable for steep tapers 30

308765 30

Pull stud sealed suitable for steep tapers 40

308660 40

Special pull stud with internal thread suitable for steep tapers 40

308740 40

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50

308605 50

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40

308812 40

Pull stud Form B suitable for steep tapers 40

308640 40

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40

308801 40