

Garant
Whistle Notch arbor Form ADB, SK 40 short, Clamping range Ø D1: 12 mm

Order data

Order number	300430 12
GTIN	4045197284433
Item class	31A

Description
Version:

With back stop screw. Shanks hard turned (smooth cutting action). With Balluffchip bore.

Feature:

The tool is firmly clamped at the side with the clamping screw and supported at the back with the back stop screw. Clamping free of play, giving low vibration running.

Advantage:

The tool is firmly clamped at the side with the clamping screw and supported at the back with the back stop screw. Clamping free of play, giving low vibration running.

Application:

For clamping tools with parallel shank **and whistle notch shanks** (2°) to DIN 1835 E and DIN 6535 HE.

- **The loss of length due to regrinding of the drill front can be corrected by axial length adjustment in the toolholder.**

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 50 mm

External Ø D: 42 mm

Spare clamping screw No. 30 9900: 12

Technical description

Overhang dimension A	50 mm
Spare clamping screw No. 30 9900	12

Clamping $\varnothing D_1$	12 mm
External $\varnothing D$	42 mm
Adapter	SK 40 short
Standard	DIN 6359
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 6.3 at 25,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Pull stud Form A suitable for steep tapers 40	308600 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud sealed, form B suitable for steep tapers 40	308650 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
	308812 40

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40

Pull stud sealed suitable for steep tapers 40 308660 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40 308630 40

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40 308820 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40 308802 40

Pull stud Form B suitable for steep tapers 40 308640 40

Pull stud Hurco 60° with fit sealed suitable for steep tapers 40 308804 40

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40 308615 40

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40 308801 40

Wrench for pull studs ISO 7388 suitable for ISO taper size 40 308830 40

Pull stud Mazak sealed, form A suitable for steep tapers 40M 308670 40M

Special pull stud with no internal thread sealed suitable for steep tapers 40 308700 40

Pull stud 90° sealed suitable for steep tapers 40 308795 40

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40 308806 40

Pull stud 60° sealed suitable for steep tapers 40 308785 40

Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40 308810 40

Special pull stud with internal thread suitable for steep tapers 40 308740 40

Pull stud sealed suitable for steep tapers 40 308635 40

Pull stud 90° sealed suitable for steep tapers 40 308790 40

Spare clamping screw for chucks with clamping Ø D1 12 mm 309900 12

