

**Garant**
**Whistle Notch arbor Form ADB, SK 40 short, Clamping range Ø D1: 6 mm**

**Order data**

Order number	300430 6
GTIN	4045197284389
Item class	31A

**Description**
**Version:**

With back stop screw. Shanks hard turned (smooth cutting action). With Balluffchip bore.

**Feature:**

The tool is firmly clamped at the side with the clamping screw and supported at the back with the back stop screw. Clamping free of play, giving low vibration running.

**Advantage:**

The tool is firmly clamped at the side with the clamping screw and supported at the back with the back stop screw. Clamping free of play, giving low vibration running.

**Application:**

For clamping tools with parallel shank **and whistle notch shanks** (2°) to DIN 1835 E and DIN 6535 HE.

- **The loss of length due to regrinding of the drill front can be corrected by axial length adjustment in the toolholder.**

**Optional extras:**

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 50 mm

External Ø D: 25 mm

Spare clamping screw No. 30 9900: 6

**Technical description**

Spare clamping screw No. 30 9900	6
Clamping Ø D <sub>1</sub>	6 mm

Overhang dimension A	50 mm
External Ø D	25 mm
Adapter	SK 40 short
Standard	DIN 6359
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 6.3 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HPC
Type of product	Side lock arbor

## Accessories

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud Form B suitable for steep tapers 40	308640 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Pull stud sealed suitable for steep tapers 40	308635 40
	308630 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40

Pull stud 90° sealed suitable for steep tapers 40	308795 40
---	-----------

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
--	-----------

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
--	-----------

Pull stud Form A suitable for steep tapers 40	308600 40
---	-----------

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
---	-----------

Pull stud sealed, form B suitable for steep tapers 40	308650 40
---	-----------

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
--	-----------

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
---	-----------

Pull stud 90° sealed suitable for steep tapers 40	308790 40
---	-----------

Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
--	-----------

Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
--	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
---	-----------

Pull stud sealed, form B suitable for steep tapers 40	308620 40
---	-----------

Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
---	-----------

Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
--	------------

Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
---	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
---	-----------

Pull stud 60° sealed suitable for steep tapers 40	308785 40
---	-----------

Pull stud 45° sealed suitable for steep tapers 40	308760 40
---	-----------

Spare clamping screw for chucks with clamping Ø D1 6 mm	309900 6
---	----------