

FAHRION®
PRÄZISION
Precision ER collet chuck CENTRO P, SK 40 A = 70, Type CP for ER: 40AD

Order data

Order number	300687 40AD
GTIN	4054631060281
Item class	33F

Description
Version:

- **External and internal tapers ground. With Balluffchip- bore.**
- **Radial run-out and repetition accuracy 3µm at 3 × D, maximum 50 mm.**
- **Very high clamping forces due to the collet fully seated in the chuck and coated clamping nut.**
- **Vibration damping due to the element collet and mass of the chuck.**
- **Alternatively without seals with ER CP clamping nut No. 309655 or sealed system with ER clamping nut CP for HP sealing rings No. 309665 in conjunction with HP sealing rings No.309666 – 309668 (for internal coolant supply or as a dirt trap!).**

Advantage:

Patented optimum seating of the collet, double guides, trapezoidal thread and low-friction coated clamping nut amalgamate when clamped into a sturdy unit, thus ensuring a very high degree of rigidity and precision.

Application:

For high precision clamping of tools with plain shank.

Supplied with:

Without clamping nut, without sealing rings.

Optional extras:

Pull-studs (PS) No. 308600 – 308806, PS pull stud wrenches No. 308820; 308835, precision ER collets for HP No. 309368 – 309378, and for taps No. 309402 – 309418 (not for Horex), ER CP clamping nuts No. 309655; 309665, HP sealing rings No. 309666 – 309668. CP roller bearing wrenches No. 309754; 309756.

Note:

- **CP chuck clamps only nominal Ø up to shank Ø tolerance h10.**
- **Use in combination with Fahrion collets.**

Machining strategy: HSC

Shape: AD
Clamping range: 3 - 26 mm
External Ø D: 63 mm

Technical description

Clamping range	3 - 26 mm
Type CP for ER	40AD
External Ø D	63 mm
Shape	AD
Series	Centro P
Adapter	SK 40 A = 70
Arbor standard	ISO 7388-1
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity ER collet with CP collet chuck	≤ 6 µm
Concentricity HP collet with CP collet chuck	≤ 3 µm
Machining strategy	HSC
Type of product	Collet chuck