

**Garant**
**Milling head arbor Form ADB with cooling channel bores, SK 30 short, Spigot  
 Ø d1: 22 mm**

**Order data**

Order number	301013 22
GTIN	4045197944221
Item class	31A

**Description**
**Version:**

- From clamping Ø 40 with 4 tapped holes for face mills to DIN 2079.
- Taper shank, spigot, and all contact surfaces ground at the collar.
- Short series.
- Increased collar contact surface.
- With Balluffchip bore.
- With 4 cooling channel bores.
- All shanks hard turned (for smooth running!).

**Supplied with:**

Lock screw.

**Optional extras:**

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

Overhang dimension A: 50 mm

External Ø D: 48 mm

Milling mandrel length  $L_4$ : 19 mm

Spare milling cutter lock screw No. 309860: 22

**Technical description**

Overhang dimension A	50 mm
Suitable toggle spanner No. 309840	22

Spare milling cutter lock screw No. 309860	22
Milling mandrel length L <sub>4</sub>	19 mm
External Ø D	48 mm
Spigot Ø d <sub>1</sub>	22 mm
Adapter	SK 30 short
Standard	DIN 6357
Arbor standard	DIN 69871
Arbor standard	ISO 7388-1
Shape	ADB
Cooling channel bore	not pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Type of product	Milling head arbor