

Garant
Milling head arbor cylindrical, SK 50 A = 300, Spigot Ø d1: 40 mm

Order data

Order number	301147 40
GTIN	4045197926821
Item class	31A

Description
Version:

- Shank, spigot, and all contact surfaces are ground at the collar.
- With Balluffchip bore.
- Larger collar contact face.
- Vibration damped version, arbor with vibration-damping core.

Vibration damped version, arbor with vibration-damping core.

Advantage:

Significantly lower tendency to vibrate! Considerable increase in feed rate!

Supplied with:

Cutter lock screw and drive dog.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

Note:

Further sizes on request.

Ø D₂: 89 mm

Milling mandrel length L₄: 28 mm

Technical description

Milling mandrel length L ₄	28 mm
Spigot Ø d ₁	40 mm
Ø D ₂	89 mm
Adapter	SK 50 A = 300
Standard	DIN 6357

Arbor standard	DIN 69871
Arbor standard	ISO 7388-1
Shape	A
Balance quality G at rotational speed	G 6.3 at 8,000 rpm
Concentricity	$\leq 6 \mu\text{m}$
Machining strategy	HPC
Vibration	damped
Type of product	Milling head arbor