

Garant

**Milling head arbor cylindrical, with cooling channel bore, SK 50 A = 200,
Spigot Ø d1: 16 mm**



Order data

Order number	301151 16
GTIN	4045197942265
Item class	31A

Description

Version:

- Shank, spigot, and all contact surfaces are ground at the collar.
- With Balluffchip bore.
- Larger collar contact face.
- Vibration damped version, arbor with vibration-damping core.

Vibration damped version, arbor with vibration-damping core.

Advantage:

Significantly lower tendency to vibrate. Considerable increase in feed rate.

Supplied with:

Cutter lock screw and drive dog.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

Note:

Further sizes on request.

Ø D₂: 38 mm

Milling mandrel length L₄: 17 mm

Technical description

Milling mandrel length L ₄	17 mm
Spigot Ø d ₁	16 mm
Ø D ₂	38 mm
Adapter	SK 50 A = 200

Standard	DIN 6357
Arbor standard	DIN 69871
Arbor standard	ISO 7388-1
Shape	AD
Balance quality G at rotational speed	G 6.3 at 8,000 rpm
Concentricity	≤ 6 μm
Machining strategy	HPC
Vibration	damped
Type of product	Milling head arbor