

## Garant

**Milling head arbor cylindrical, with cooling channel bore, SK 50 A = 200,  
Spigot Ø d1: 22 mm**



### Order data

Order number	301151 22
GTIN	4045197942272
Item class	31A

### Description

#### Version:

- Shank, spigot, and all contact surfaces are ground at the collar.
- With Balluffchip bore.
- Larger collar contact face.
- Vibration damped version, arbor with vibration-damping core.

**Vibration damped version, arbor with vibration-damping core.**

#### Advantage:

Significantly lower tendency to vibrate. Considerable increase in feed rate.

#### Supplied with:

Cutter lock screw and drive dog.

#### Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

#### Note:

Further sizes on request.

Ø D<sub>2</sub>: 48 mm

Milling mandrel length L<sub>4</sub>: 19 mm

### Technical description

Spigot Ø d <sub>1</sub>	22 mm
Ø D <sub>2</sub>	48 mm
Milling mandrel length L <sub>4</sub>	19 mm
Adapter	SK 50 A = 200

Standard	DIN 6357
Arbor standard	DIN 69871
Arbor standard	ISO 7388-1
Shape	AD
Balance quality G at rotational speed	G 6.3 at 8,000 rpm
Concentricity	≤ 6 μm
Machining strategy	HPC
Vibration	damped
Type of product	Milling head arbor