

Garant
MT reducing adapter with tang, Form AD, SK 40 short, MT internal: 2

Order data

Order number	301155 2
GTIN	4045197285881
Item class	31A

Description
Version:

- **Ground internally and externally.**
- **With Balluffchip bore.**

GARANT –All shanks hard turned (for smooth cutting action!).

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835.

Concentricity: $\leq 8 \mu\text{m}$

Overhang dimension A: 50 mm

External \varnothing D: 32 mm

Technical description

Overhang dimension A	50 mm
Morse taper internal	2
External \varnothing D	32 mm
Adapter	SK 40 short
Arbor standard	ISO 7388-1
Shape	AD
Balance quality G at rotational speed	G 6.3 at 12,000 rpm
Concentricity	$\leq 8 \mu\text{m}$

Type of product	Arbor adapter
-----------------	---------------

Accessories

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Pull stud Form B suitable for steep tapers 40	308640 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud Form A suitable for steep tapers 40	308600 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud sealed suitable for steep tapers 40	308635 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
	308670 40M

Pull stud Mazak sealed, form A suitable for steep tapers
40M

Pull stud Hurco 45° with fit sealed suitable for steep tapers
40

308802 40

Pull stud 60° sealed suitable for steep tapers 40

308785 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers
40

308630 40

Pull stud 45° sealed suitable for steep tapers 40

308765 40

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40

308605 40

Torque insert for Pull studs to SO 7388 suitable for ISO
taper size 40

308812 40

Pull stud sealed, form B suitable for steep tapers 40

308650 40

Special pull stud with internal thread suitable for steep
tapers 40

308740 40