

**Garant**
**MT reducing adapter with tang, Form AD, SK 40 short, MT internal: 4**

**Order data**

Order number	301155 4
GTIN	4045197285904
Item class	31A

**Description**
**Version:**

- **Ground internally and externally.**
- **With Balluffchip bore.**

**GARANT** –All shanks hard turned (for smooth cutting action!).

**Optional extras:**

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835.

Concentricity:  $\leq 8 \mu\text{m}$

Overhang dimension A: 95 mm

External  $\varnothing$  D: 48 mm

**Technical description**

Overhang dimension A	95 mm
Morse taper internal	4
External $\varnothing$ D	48 mm
Adapter	SK 40 short
Arbor standard	ISO 7388-1
Shape	AD
Balance quality G at rotational speed	G 6.3 at 12,000 rpm
Concentricity	$\leq 8 \mu\text{m}$

Type of product	Arbor adapter
-----------------	---------------

## Accessories

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
--	-----------

Pull stud 90° sealed suitable for steep tapers 40	308795 40
---	-----------

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
--	-----------

Special pull stud with internal thread suitable for steep tapers 40	308740 40
---	-----------

Pull stud 90° sealed suitable for steep tapers 40	308790 40
---	-----------

Pull stud 45° sealed suitable for steep tapers 40	308760 40
---	-----------

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
--	-----------

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
---	-----------

Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
--	-----------

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
--	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
---	-----------

Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
--	-----------

Pull stud Form A suitable for steep tapers 40	308600 40
---	-----------

Pull stud sealed, form B suitable for steep tapers 40	308650 40
---	-----------

Pull stud sealed suitable for steep tapers 40	308660 40
---	-----------

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
--	-----------

Pull stud sealed suitable for steep tapers 40	308635 40
---	-----------

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
--	-----------

	308830 40
--	-----------

Wrench for pull studs ISO 7388 suitable for ISO taper size 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40

308630 40

Special pull stud with no internal thread sealed suitable for steep tapers 40

308720 40

Pull stud Form B suitable for steep tapers 40

308640 40

Pull stud 60° sealed suitable for steep tapers 40

308785 40

Pull stud Mazak sealed, form A suitable for steep tapers 40M

308670 40M

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40

308625 40

Pull stud sealed, form B suitable for steep tapers 40

308620 40

Pull stud 45° sealed suitable for steep tapers 40

308765 40