

**Garant**
**MT reducing adapter with tang, Form AD, SK 50 short, MT internal: 2**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 301170 2      |
| GTIN         | 4045197285911 |
| Item class   | 31A           |

**Description**
**Version:**

- **Ground internally and externally.**
- **With Balluffchip bore.**

**GARANT** –All shanks hard turned (for smooth cutting action!).

**Optional extras:**

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835.

Concentricity:  $\leq 8 \mu\text{m}$

Overhang dimension A: 60 mm

External  $\varnothing$  D: 32 mm

**Technical description**

|                                       |                      |
|---------------------------------------|----------------------|
| Morse taper internal                  | 2                    |
| Overhang dimension A                  | 60 mm                |
| External $\varnothing$ D              | 32 mm                |
| Adapter                               | SK 50 short          |
| Arbor standard                        | ISO 7388-1           |
| Shape                                 | AD                   |
| Balance quality G at rotational speed | G 6.3 at 12,000 rpm  |
| Concentricity                         | $\leq 8 \mu\text{m}$ |

|                 |               |
|-----------------|---------------|
| Type of product | Arbor adapter |
|-----------------|---------------|

## Accessories

|  |           |
|--|-----------|
| Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50                         | 308615 50 |
| Pull stud sealed, form B suitable for steep tapers 50                                    | 308620 50 |
| Pull stud sealed suitable for steep tapers 50  | 308660 50 |
| Pull stud stud sealed, form A suitable for steep tapers 50                               | 308610 50 |
| Special pull stud with internal thread suitable for steep tapers 50                      | 308740 50 |
| Pull stud Form A suitable for steep tapers 50  | 308600 50 |
| Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50 | 308820 50 |
| Pull stud 45° sealed suitable for steep tapers 50  | 308760 50 |
| Pull stud 45° sealed suitable for steep tapers 50  | 308765 50 |
| Pull stud Form B suitable for steep tapers 50  | 308640 50 |
| Pull stud sealed, form B suitable for steep tapers 50                                    | 308650 50 |
| Special pull stud with no internal thread sealed suitable for steep tapers 50            | 308720 50 |
| Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50                 | 308810 50 |
| Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50                   | 308812 50 |
| Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50                                 | 308605 50 |
| Special pull stud with no internal thread sealed suitable for steep tapers 50            | 308700 50 |
| Pull stud 90° sealed suitable for steep tapers 50  | 308795 50 |
| Wrench for pull studs ISO 7388 suitable for ISO taper size 50                            | 308830 50 |
| Pull stud 60° sealed suitable for steep tapers 50  | 308785 50 |

Pull stud 90° sealed suitable for steep tapers 50

308790 50