

Garant
MT reducing adapter with tang, Form AD, SK 50 short, MT internal: 4

Order data

Order number	301170 4
GTIN	4045197285935
Item class	31A

Description
Version:

- **Ground internally and externally.**
- **With Balluffchip bore.**

GARANT –All shanks hard turned (for smooth cutting action!).

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835.

Concentricity: $\leq 8 \mu\text{m}$

Overhang dimension A: 95 mm

External \varnothing D: 48 mm

Technical description

Morse taper internal	4
Overhang dimension A	95 mm
External \varnothing D	48 mm
Adapter	SK 50 short
Arbor standard	ISO 7388-1
Shape	AD
Balance quality G at rotational speed	G 6.3 at 12,000 rpm
Concentricity	$\leq 8 \mu\text{m}$

Type of product	Arbor adapter
-----------------	---------------

Accessories

Pull stud 90° sealed suitable for steep tapers 50	308790 50
---	-----------

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50	308605 50
--	-----------

Pull stud Form A suitable for steep tapers 50	308600 50
---	-----------

Pull stud 90° sealed suitable for steep tapers 50	308795 50
---	-----------

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50	308812 50
--	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
---	-----------

Pull stud 45° sealed suitable for steep tapers 50	308765 50
---	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 50	308700 50
---	-----------

Pull stud sealed suitable for steep tapers 50	308660 50
---	-----------

Pull stud 60° sealed suitable for steep tapers 50	308785 50
---	-----------

Special pull stud with internal thread suitable for steep tapers 50	308740 50
---	-----------

Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
--	-----------

Pull stud Form B suitable for steep tapers 50	308640 50
---	-----------

Pull stud 45° sealed suitable for steep tapers 50	308760 50
---	-----------

Pull stud sealed, form B suitable for steep tapers 50	308650 50
---	-----------

Pull stud sealed, form B suitable for steep tapers 50	308620 50
---	-----------

Pull stud stud sealed, form A suitable for steep tapers 50	308610 50
--	-----------

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
--	-----------

Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50
---	-----------

	308820 50
--	-----------

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872)
suitable for ISO taper size 50
