

**Garant**
**Short drill chuck Form AD, SK 40, Clamping range: 1-16 mm**

**Order data**

Order number	301425 1-16
GTIN	4045197931795
Item class	31B

**Description**
**Version:**

For clockwise and anticlockwise rotation.

With Balluffchip bore. Maximum radial run-out  $\leq 20 \mu\text{m}$ .

Sandblasted and ground.

- **slim design.**
- **targeted coolant transfer to tools with IC.**
- **Optimum holding torques at the tool.**

**Supplied with:**

**Torx® chuck key** with T-handle **for high clamping force.**

**Optional extras:**

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

maximum tightening torque  $M_{d\text{max}}$ :  $\leq 14 \text{ Nm}$

Type: slim

Overhang dimension A: 80 mm

External  $\varnothing$  D: 50 mm

Spare Torx® chuck key No. 625220: TX25

**Technical description**

Type	slim
Clamping range	1 - 16 mm
Spare Torx® chuck key No. 625220	TX25
Overhang dimension A	80 mm

External Ø D	50 mm
Adapter	SK 40
Arbor standard	ISO 7388-1
Shape	AD
Through-coolant	yes, with max. 50 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 20 µm
maximum tightening torque $M_{d\max}$	≤ 14 Nm
Type of product	Short drill chuck