

**Garant**
**Short drill chuck Form AD/B, SK 40, Clamping range: 0,3-10 mm**

**Order data**

Order number	301465 0,3-10
GTIN	4045197868787
Item class	31B

**Description**
**Version:**

For clockwise and anticlockwise rotation.

With Balluffchip bore. Maximum radial run-out  $\leq 20 \mu\text{m}$ .

Glass bead blasted. Slim design for the most popular  $\varnothing$  up to 10.2 mm.

**Supplied with:**

**Clamping wrench** with T-handle.

**Optional extras:**

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

maximum tightening torque  $M_{d\text{max}}: \leq 14 \text{ Nm}$

Type: slim

Overhang dimension A: 73 mm

External  $\varnothing$  D: 38 mm

Spare chuck key No. 627425: 4 AF

**Technical description**

External $\varnothing$ D	38 mm
Spare chuck key No. 627425	4 AF
Overhang dimension A	73 mm
Clamping range	0.3 - 10.2 mm
Type	slim
Adapter	SK 40

Arbor standard	ISO 7388-1
Shape	ADB
Through-coolant	yes, with max. 50 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 20 µm
maximum tightening torque $M_{d,max}$	≤ 14 Nm
Type of product	Short drill chuck

## Accessories

Pull stud Form B suitable for steep tapers 40	308640 40
Pull stud Form A suitable for steep tapers 40	308600 40
Pull stud sealed suitable for steep tapers 40	308635 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull stud sealed, form B suitable for steep tapers 40	308650 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
	308806 40

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40