

Garant
Short drill chuck Form AD/B, SK 40, Clamping range: 0,5-16 mm

Order data

| | |
|--------------|---------------|
| Order number | 301465 0,5-16 |
| GTIN | 4045197573407 |
| Item class | 31B |

Description
Version:

For clockwise and anticlockwise rotation.

With Balluffchip bore. Maximum radial run-out $\leq 20 \mu\text{m}$.

Glass bead blasted.

Supplied with:

Clamping wrench with T-handle.

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

maximum tightening torque $M_{d\text{max}} \leq 14 \text{ Nm}$

Type: Standard

Overhang dimension A: 90 mm

External \varnothing D: 57 mm

Spare chuck key No. 627425: SW 6

Technical description

| | |
|----------------------------|-------------|
| Spare chuck key No. 627425 | SW 6 |
| Type | Standard |
| Clamping range | 0.5 - 16 mm |
| Overhang dimension A | 90 mm |
| External \varnothing D | 57 mm |
| Adapter | SK 40 |

| | |
|---------------------------------------|-----------------------|
| Arbor standard | ISO 7388-1 |
| Shape | ADB |
| Through-coolant | yes, with max. 50 bar |
| Balance quality G at rotational speed | G 2.5 at 25,000 rpm |
| Concentricity | ≤ 20 µm |
| maximum tightening torque $M_{d,max}$ | ≤ 14 Nm |
| Type of product | Short drill chuck |

Accessories

| | |
|---|-----------|
| Pull stud Hurco 90° with fit sealed suitable for steep tapers 40 | 308806 40 |
| Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40 | 308630 40 |
| Pull stud 90° sealed suitable for steep tapers 40 | 308795 40 |
| Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40 | 308810 40 |
| Pull stud sealed suitable for steep tapers 40 | 308635 40 |
| Pull-stud 60° sealed suitable for steep tapers 40 | 308780 40 |
| Pull stud Form B suitable for steep tapers 40 | 308640 40 |
| Pull stud Form A suitable for steep tapers 40 | 308600 40 |
| Pull stud sealed, form B suitable for steep tapers 40 | 308650 40 |
| Pull stud 45° sealed suitable for steep tapers 40 | 308760 40 |
| Pull stud stud sealed, form A suitable for steep tapers 40 | 308610 40 |
| Pull stud 60° sealed suitable for steep tapers 40 | 308785 40 |
| Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40 | 308801 40 |
| Pull stud Hurco 60° with fit sealed suitable for steep tapers 40 | 308804 40 |
| Pull stud Hurco 45° with fit sealed suitable for steep tapers 40 | 308802 40 |

| | |
|--|------------|
| Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40 | 308625 40 |
| Pull stud 45° sealed suitable for steep tapers 40 | 308765 40 |
| Pull stud sealed, form B suitable for steep tapers 40 | 308620 40 |
| Pull stud Mazak sealed, form A suitable for steep tapers 40M | 308670 40M |
| Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40 | 308803 40 |
| Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40 | 308812 40 |
| Pull stud sealed suitable for steep tapers 40 | 308660 40 |
| Special pull stud with no internal thread sealed suitable for steep tapers 40 | 308720 40 |
| Wrench for pull studs ISO 7388 suitable for ISO taper size 40 | 308830 40 |
| Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40 | 308820 40 |
| Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40 | 308605 40 |
| Special pull stud with internal thread suitable for steep tapers 40 | 308740 40 |
| Pull stud 90° sealed suitable for steep tapers 40 | 308790 40 |
| Special pull stud with no internal thread sealed suitable for steep tapers 40 | 308700 40 |
| Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40 | 308615 40 |
| Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40 | 308805 40 |