

Garant
Short drill chuck Form AD/B, SK 50, Clamping range: 0,5-16 mm

Order data

Order number	301467 0,5-16
GTIN	4045197573414
Item class	31B

Description
Version:

For clockwise and anticlockwise rotation.

With Balluffchip bore. Maximum radial run-out $\leq 20 \mu\text{m}$.

Glass bead blasted.

Supplied with:

Clamping wrench with T-handle.

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

maximum tightening torque $M_{d\text{max}} \leq 14 \text{ Nm}$

Type: Standard

Overhang dimension A: 106 mm

External \varnothing D: 57 mm

Spare chuck key No. 627425: SW 6

Technical description

Clamping range	0.5 - 16 mm
Overhang dimension A	106 mm
Type	Standard
Spare chuck key No. 627425	SW 6
External \varnothing D	57 mm
Adapter	SK 50

Arbor standard	ISO 7388-1
Shape	ADB
Through-coolant	yes, with max. 50 bar
Balance quality G at rotational speed	G 2.5 at 18,000 rpm
Concentricity	≤ 20 µm
maximum tightening torque $M_{d,max}$	≤ 14 Nm
Type of product	Short drill chuck

Accessories

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50	308812 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
Pull stud Form A suitable for steep tapers 50	308600 50
Pull stud 45° sealed suitable for steep tapers 50	308760 50
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50	308605 50
Pull stud sealed, form B suitable for steep tapers 50	308620 50
Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50
Pull stud sealed, form B suitable for steep tapers 50	308650 50
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50	308820 50
Pull stud sealed suitable for steep tapers 50	308660 50
Pull stud stud sealed, form A suitable for steep tapers 50	308610 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308700 50
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50

Pull stud Form B suitable for steep tapers 50	308640 50
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
Pull-stud 60° sealed suitable for steep tapers 50	308780 50
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Special pull stud with internal thread suitable for steep tapers 50	308740 50
Pull stud 45° sealed suitable for steep tapers 50	308765 50