



## Short drill chuck Form A, SK 40, Clamping range: 2,5-16 mm



### Order data

Order number	301480 2,5-16
GTIN	4045197307637
Item class	37D

### Description

#### Version:

For clockwise and anticlockwise rotation.  
Burnished.

#### Supplied with:

Hexagon screwdriver with T-handle.

#### Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 104.5 mm

External Ø D: 56 mm

Spare chuck key No. 627425: SW6

### Technical description

Clamping range	2.5 - 16 mm
Spare chuck key No. 627425	SW6
Overhang dimension A	104.5 mm
External Ø D	56 mm
Adapter	SK 40
Arbor standard	ISO 7388-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 18,000 rpm

maximum tightening torque $M_{d\max}$	≤ 14 Nm
Type of product	Short drill chuck

## Accessories

Special pull stud with internal thread suitable for steep tapers 40	308740 40
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud Form B suitable for steep tapers 40	308640 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud Form A suitable for steep tapers 40	308600 40
Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
Pull stud sealed suitable for steep tapers 40	308660 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Pull stud sealed, form B suitable for steep tapers 40	308650 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40