



Short drill chuck Form A, SK 50, Clamping range: 2,5-16 mm



Order data

Order number	301500 2,5-16
GTIN	4045197307651
Item class	37D

Description

Version:

For clockwise and anticlockwise rotation.
Burnished.

Supplied with:

Hexagon screwdriver with T-handle.

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 106.5 mm

External Ø D: 56 mm

Spare chuck key No. 627425: SW6

Technical description

Clamping range	2.5 - 16 mm
Spare chuck key No. 627425	SW6
Overhang dimension A	106.5 mm
External Ø D	56 mm
Adapter	SK 50
Arbor standard	ISO 7388-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 18,000 rpm

maximum tightening torque $M_{d\max}$	≤ 14 Nm
Type of product	Short drill chuck

Accessories

Pull stud stud sealed, form A suitable for steep tapers 50	308610 50
Pull-stud 60° sealed suitable for steep tapers 50	308780 50
Pull stud sealed, form B suitable for steep tapers 50	308620 50
Pull stud Form B suitable for steep tapers 50	308640 50
Pull stud 45° sealed suitable for steep tapers 50	308760 50
Pull stud sealed, form B suitable for steep tapers 50	308650 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308700 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
Pull stud sealed suitable for steep tapers 50	308660 50
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Pull stud Form A suitable for steep tapers 50	308600 50
Special pull stud with internal thread suitable for steep tapers 50	308740 50