

Garant
Slim hydraulic chuck, SK 40 A = 160, Clamping range \varnothing D1: 8 mm

Order data

Order number	302095 8
GTIN	4045197868633
Item class	31A

Description
Version:

- **Extremely slim design (3° contour)**
- **Processed surface structure.**
- **With Balluffchip bore.**
- **Axial length adjustment facility.**
- **Shanks hard turned.**
- **Reducing adapters can be used.**

Application:

Especially for tool and mould making. **Wherever reduced interference contours are required.** For drilling, reaming, and milling. For clamping tools with shank tolerance h6.

Supplied with:

Hexagon socket drive with T-handle.

Optional extras:

Pull studs (AB) No. 308600 – 308806, AB pull stud wrenches No. 308820 / 308835, Reducing sleeves No. 302135 – 302180.

Machining strategy: HPC

\varnothing D₂: 18 mm

\varnothing D₃: 35.4 mm

External \varnothing D: 49.5 mm

L₂: 119.5 mm

Technical description

External \varnothing D	49.5 mm
\varnothing D ₂	18 mm

Clamping $\varnothing D_1$	8 mm
L_2	119.5 mm
$\varnothing D_3$	35.4 mm
Adapter	SK 40 A = 160
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HSC
Machining strategy	HPC
Balluffchip bore	yes
Type of product	Hydraulic clamping chuck

Accessories

Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
ER chuck key 1/2 inch socket for ER collet chuck 40	309700 40
Pull stud Form A suitable for steep tapers 40	308600 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
ER chuck key for ER collet chuck 40	309680 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
	308810 40

Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40

Pull stud sealed suitable for steep tapers 40	308660 40
---	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
---	-----------

Pull stud 45° sealed suitable for steep tapers 40	308760 40
---	-----------

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
--	-----------

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
--	-----------

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
--	-----------

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
--	-----------

Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
---	-----------

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
--	-----------

Pull stud 45° sealed suitable for steep tapers 40	308765 40
---	-----------

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
--	-----------

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
---	-----------

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
---	-----------

Pull stud sealed, form B suitable for steep tapers 40	308620 40
---	-----------

Pull stud sealed suitable for steep tapers 40	308635 40
---	-----------

Pull stud Form B suitable for steep tapers 40	308640 40
---	-----------

Pull stud 90° sealed suitable for steep tapers 40	308790 40
---	-----------

Pull stud sealed, form B suitable for steep tapers 40	308650 40
---	-----------