

**Garant**
**Shrink-fit chuck, SK 30 short, Clamping range  $\varnothing$  D1: 3 mm**

**Order data**

Order number	302225 3
GTIN	2050001838919
Item class	31A

**Description**
**Version:**

- **High-temperature steel.**
- **Size 3 -5 for carbide, from size 6 for HSS and carbide.**
- **All shanks hard turned (for smooth running!).**
- **With Balluffchip bore.**

**Application:**

For clamping tools with parallel shank to h6 tolerance.  
Suitable for inductive, contact, and hot-air shrink units.

**Optional extras:**

Pull studs (PS) No. 308600 – 308800. PS wrenches No. 308820 – 308835, Shrink-fit chuck extensions No. 302410 – 302419. Shrink-fit units, accessories No. 354210 – 354450, balancing screws set No. 309906 size 180.

Machining strategy: HPC

Overhang dimension A: 80 mm

External  $\varnothing$  D: 17 mm

$\varnothing$  D<sub>2</sub>: 10 mm

**Technical description**

Overhang dimension A	80 mm
External $\varnothing$ D	17 mm
$\varnothing$ D <sub>2</sub>	10 mm
Clamping $\varnothing$ D <sub>1</sub>	3 mm

Adapter	SK 30 short
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Shrink-fit chuck

## Accessories

Cooling unit Type CU1	354215 CU1
Pull stud stud sealed, form A suitable for steep tapers 30	308610 30
Pull stud 45° sealed suitable for steep tapers 30	308765 30
Pull stud 60° sealed suitable for steep tapers 30	308785 30
Shrink-fit chuck extension 4.5° without length adjustment screw Ø d / Ø D1 16/3 mm	302410 16/3
Shrink-fit chuck extension 4.5° without length adjustment screw Ø d / Ø D1 12/3 mm	302410 12/3
Shrink-fit unit Type SU1	354210 SU1
Pull stud 45° sealed suitable for steep tapers 30	308760 30