

Garant
Shrink-fit chuck with cooling channel bores, SK 40 ultra short, Clamping range \varnothing D1: 25 mm

Order data

Order number	302230 25
GTIN	4045197467690
Item class	31A

Description
Version:

- **High-temperature steel.**
- **Size 3 -5 for carbide, from size 6 for HSS and carbide.**
- **All shanks hard turned (for smooth running!).**
- **With Balluffchip bore.**

Ultra-short version for more stability and less vibration.

With **coolant hole bores** tapped for plugging.

Coolant hole bores at clamping \varnothing D1: 3, 4 and 5 mm cannot be plugged.

This results in a longer tool life and better surface qualities. Without length adjustment screw.

Application:

For clamping tools with parallel shank to h6 tolerance.

Suitable for inductive, contact, and hot-air shrink units.

Optional extras:

Pull studs (PS) No. 308600 – 308800. PS wrenches No. 308820 – 308835, Shrink-fit chuck extensions No. 302410 – 302419. Shrink-fit units, accessories No. 354210 – 354450, balancing screws set No. 309906 size 180.

Note:

No length adjustment available.

Machining strategy: HPC

Cooling channel bore: lockable

Overhang dimension A: 75 mm

External \varnothing D: 50 mm

\varnothing D₂: 45 mm

Technical description

Ø D ₂	45 mm
Clamping Ø D ₁	25 mm
Overhang dimension A	75 mm
External Ø D	50 mm
Cooling channel bore	lockable
Adapter	SK 40 ultra short
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Shrink-fit chuck

Accessories

Pull stud sealed, form B suitable for steep tapers 40	308650 40
Pull stud sealed suitable for steep tapers 40	308635 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Pull stud Form B suitable for steep tapers 40	308640 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Screening plate for coil SU1 for clamping Ø 20-32 mm	354240 20-32

Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Cooling unit Type CU1	354215 CU1
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Cooling adapter short 4.5° for clamping Ø 22,1-32 mm	354235 22,1-32
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud Form A suitable for steep tapers 40	308600 40
Pull stud sealed suitable for steep tapers 40	308660 40
Basic tool mounting for SK for SK taper shank 40 SK	354225 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Shrink-fit unit Type SU1	354210 SU1
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Cooling adapter long 4.5° for clamping Ø 22,1-32 mm	354236 22,1-32
	308670 40M

Pull stud Mazak sealed, form A suitable for steep tapers
40M

Special pull stud with no internal thread sealed suitable for
steep tapers 40

308720 40