

Garant
Shrink-fit chuck, SK 40 short, Clamping range \varnothing D1: 8 mm

Order data

Order number	302235 8
GTIN	4045197288301
Item class	31A

Description
Version:

- **High-temperature steel.**
- **Size 3 -5 for carbide, from size 6 for HSS and carbide.**
- **All shanks hard turned (for smooth running!).**
- **With Balluffchip bore.**

Application:

For clamping tools with parallel shank to h6 tolerance.
Suitable for inductive, contact, and hot-air shrink units.

Optional extras:

Pull studs (PS) No. 308600 – 308800. PS wrenches No. 308820 – 308835, Shrink-fit chuck extensions No. 302410 – 302419. Shrink-fit units, accessories No. 354210 – 354450, balancing screws set No. 309906 size 180.

Overhang dimension A: 80 mm

External \varnothing D: 27 mm

\varnothing D₂: 21 mm

Technical description

Clamping \varnothing D ₁	8 mm
Overhang dimension A	80 mm
\varnothing D ₂	21 mm
External \varnothing D	27 mm

Adapter	SK 40 short
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Shrink-fit chuck

Accessories

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Shrink-fit chuck extension 4.5° with length adjustment screw Ø d / Ø D1 20/8 mm	302412 20/8
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud Form A suitable for steep tapers 40	308600 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Cooling unit Type CU1	354215 CU1
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Shrink-fit chuck extension 4.5° without length adjustment screw Ø d / Ø D1 25/8 mm	302416 25/8
Pull stud Form B suitable for steep tapers 40	308640 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
	308830 40

Wrench for pull studs ISO 7388 suitable for ISO taper size 40

Pull stud sealed suitable for steep tapers 40 308635 40

Cooling adapter long 4.5° for clamping Ø 6-9 mm 354236 6-9

Basic tool mounting for SK for SK taper shank 40 SK 354225 40

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40 308820 40

Pull stud Mazak sealed, form A suitable for steep tapers 40M 308670 40M

Pull stud sealed, form B suitable for steep tapers 40 308620 40

Pull stud 45° sealed suitable for steep tapers 40 308765 40

Pull stud 45° sealed suitable for steep tapers 40 308760 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40 308802 40

Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40 308810 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40 308630 40

Shrink-fit chuck extension 4.5° without length adjustment screw, with through coolant holes Ø d / Ø D1 25/8 mm 302414 25/8

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40 308625 40

Shrink-fit chuck extension 4.5° with length adjustment screw Ø d / Ø D1 25/8 mm 302412 25/8

Shrink-fit chuck extension 4.5° without length adjustment screw Ø d / Ø D1 25/8 mm 302410 25/8

Special pull stud with no internal thread sealed suitable for steep tapers 40 308700 40

Cooling adapter short 4.5° for clamping Ø 6-9 mm 354235 6-9

Pull stud sealed, form B suitable for steep tapers 40 308650 40

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40 308615 40

Shrink-fit chuck extension 4.5° without length adjustment screw Ø d / Ø D1 20/8 mm 302416 20/8

Pull stud 90° sealed suitable for steep tapers 40	308795 40
Shrink-fit unit Type SU1	354210 SU1
Pull stud sealed suitable for steep tapers 40	308660 40
Shrink-fit chuck extension 4.5° without length adjustment screw $\varnothing d / \varnothing D1$ 20/8 mm	302410 20/8
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Screening plate for coil SU1 for clamping \varnothing 6-12 mm	354240 6-12
Shrink fit chuck extension 3°, vibration-damped $\varnothing d / \varnothing D1$ 20/8 mm	302415 20/8
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40