

**Garant**
**Shrink-fit chuck, SK 40 A = 120, Clamping range  $\varnothing$  D1: 8 mm**

**Order data**

Order number	302256 8
GTIN	4045197287922
Item class	31A

**Description**
**Version:**

- **High-temperature steel.**
- **Size 3 -5 for carbide, from size 6 for HSS and carbide.**
- **All shanks hard turned (for smooth running!).**
- **With Balluffchip bore.**

**Application:**

For clamping tools with parallel shank to h6 tolerance.  
Suitable for inductive, contact, and hot-air shrink units.

**Optional extras:**

Pull studs (PS) No. 308600 – 308800. PS wrenches No. 308820 – 308835, Shrink-fit chuck extensions No. 302410 – 302419. Shrink-fit units, accessories No. 354210 – 354450, balancing screws set No. 309906 size 180.

Machining strategy: HPC

External  $\varnothing$  D: 27 mm

$\varnothing$  D<sub>2</sub>: 21 mm

**Technical description**

Clamping $\varnothing$ D <sub>1</sub>	8 mm
$\varnothing$ D <sub>2</sub>	21 mm
External $\varnothing$ D	27 mm
Adapter	SK 40 A = 120

Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Shrink-fit chuck

## Accessories

Pull stud 90° sealed suitable for steep tapers 40	308790 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Basic tool mounting for SK for SK taper shank 40 SK	354225 40
Shrink-fit unit Type SU1	354210 SU1
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Cooling adapter long 4.5° for clamping Ø 6-9 mm	354236 6-9
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Shrink-fit chuck extension 4.5° without length adjustment screw, with through coolant holes Ø d / Ø D1 25/8 mm	302414 25/8

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
Shrink-fit chuck extension 4.5° with length adjustment screw $\varnothing d / \varnothing D1$ 20/8 mm	302412 20/8
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull stud sealed suitable for steep tapers 40	308635 40
Pull stud Form B suitable for steep tapers 40	308640 40
Cooling adapter short 4.5° for clamping $\varnothing$ 6-9 mm	354235 6-9
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Shrink-fit chuck extension 4.5° without length adjustment screw $\varnothing d / \varnothing D1$ 25/8 mm	302410 25/8
Cooling unit Type CU1	354215 CU1
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Shrink-fit chuck extension 4.5° without length adjustment screw $\varnothing d / \varnothing D1$ 20/8 mm	302416 20/8
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud sealed, form B suitable for steep tapers 40	308650 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Shrink-fit chuck extension 4.5° with length adjustment screw $\varnothing d / \varnothing D1$ 25/8 mm	302412 25/8
	302410 20/8

Shrink-fit chuck extension 4.5° without length adjustment  
screw Ø d / Ø D1 20/8 mm

Shrink-fit chuck extension 4.5° without length adjustment  
screw Ø d / Ø D1 25/8 mm

302416 25/8

Shrink fit chuck extension 3°, vibration-damped Ø d / Ø  
D1 20/8 mm

302415 20/8

Pull stud Form A suitable for steep tapers 40

308600 40

Pull stud, 18CrNiMo7 sealed, form B suitable for steep  
tapers 40

308615 40

Screening plate for coil SU1 for clamping Ø 6-12 mm

354240 6-12