

Garant
Shrink-fit chuck, SK 40 A = 200, Clamping range \varnothing D1: 16 mm

Order data

Order number	302278 16
GTIN	4045197294289
Item class	31A

Description
Version:

- **High-temperature steel.**
- **Size 3 -5 for carbide, from size 6 for HSS and carbide.**
- **All shanks hard turned (for smooth running!).**
- **With Balluffchip bore.**

Application:

For clamping tools with parallel shank to h6 tolerance.
Suitable for inductive, contact, and hot-air shrink units.

Optional extras:

Pull studs (PS) No. 308600 – 308800. PS wrenches No. 308820 – 308835, Shrink-fit chuck extensions No. 302410 – 302419. Shrink-fit units, accessories No. 354210 – 354450, balancing screws set No. 309906 size 180.

Machining strategy: HPC

External \varnothing D: 34 mm

\varnothing D₂: 27 mm

Technical description

\varnothing D ₂	27 mm
Clamping \varnothing D ₁	16 mm
External \varnothing D	34 mm
Adapter	SK 40 A = 200

Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Shrink-fit chuck

Accessories

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Pull stud sealed suitable for steep tapers 40	308660 40
Cooling unit Type CU1	354215 CU1
Pull stud Form A suitable for steep tapers 40	308600 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Shrink-fit chuck extension 4.5° without length adjustment screw Ø d / Ø D1 25/16 mm	302410 25/16
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Pull stud sealed suitable for steep tapers 40	308635 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
	308830 40

Wrench for pull studs ISO 7388 suitable for ISO taper size 40

Shrink fit chuck extension 3°, vibration-damped $\varnothing d / \varnothing D1$ 25/16 mm

302417 25/16

Pull stud sealed, form B suitable for steep tapers 40

308620 40

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40

308806 40

Shrink-fit chuck extension 4.5° without length adjustment screw $\varnothing d / \varnothing D1$ 32/16 mm

302416 32/16

Pull stud sealed, form B suitable for steep tapers 40

308650 40

Pull stud Form B suitable for steep tapers 40

308640 40

Pull stud 45° sealed suitable for steep tapers 40

308760 40

Pull stud 90° sealed suitable for steep tapers 40

308790 40

Pull stud stud sealed, form A suitable for steep tapers 40

308610 40

Shrink-fit unit Type SU1

354210 SU1

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40

308630 40

Pull stud 90° sealed suitable for steep tapers 40

308795 40

Shrink-fit chuck extension 4.5° with length adjustment screw $\varnothing d / \varnothing D1$ 25/16 mm

302412 25/16

Screening plate for coil SU1 for clamping $\varnothing 12-20$ mm

354240 12-20

Cooling adapter short 4.5° for clamping $\varnothing 12,1-16$ mm

354235 12,1-16

Shrink-fit chuck extension 4.5° without length adjustment screw, with through coolant holes $\varnothing d / \varnothing D1$ 32/16 mm

302414 32/16

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40

308820 40

Shrink-fit chuck extension 4.5° without length adjustment screw $\varnothing d / \varnothing D1$ 32/16 mm

302410 32/16

Pull stud 45° sealed suitable for steep tapers 40

308765 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40

308625 40

Cooling adapter long 4.5° for clamping $\varnothing 12,1-16$ mm

354236 12,1-16

308670 40M

Pull stud Mazak sealed, form A suitable for steep tapers
40M

Shrink-fit chuck extension 4.5° without length adjustment
screw $\varnothing d / \varnothing D1$ 25/16 mm

302416 25/16

Shrink fit chuck extension 3°, vibration-damped $\varnothing d / \varnothing$
D1 32/16 mm

302419 32/16

Torque insert for Pull studs to SO 7388 suitable for ISO
taper size 40

308812 40

Shrink-fit chuck extension 4.5° with length adjustment
screw $\varnothing d / \varnothing D1$ 32/16 mm

302412 32/16

Basic tool mounting for SK for SK taper shank 40 SK

354225 40

Torque insert for Pull studs to DIN 69872 suitable for ISO
taper size 40

308810 40