

**Garant**
**Shrink-fit chucks slim, SK 50 A = 160, Clamping range  $\varnothing$  D1: 4 mm**

**Order data**

Order number	302344 4
GTIN	4045197505392
Item class	31A

**Description**
**Version:**

- **All shanks hard turned (for smooth running!).**
- **With Balluffchip bore.**
- **Integral tool length adjustment, range 10 mm available only from size 6 upwards!**
- **Extra slim design(reduced interference contour).**

**Application:**

- **Cutting operations in tool and mould making.**
- **For clamping tools with parallel shank to h6 tolerance.**

**Optional extras:**

Pull studs (PS) No. 308600 – 308806. PS wrenches No. 308820 – 308835, Shrink-fit chuck extensions No. 302410 – 302419. Shrink-fitting units No. 354210 – 354450.

Machining strategy: HPC

External  $\varnothing$  D: 25 mm

$\varnothing$  D<sub>2</sub>: 9 mm

**Technical description**

Clamping $\varnothing$ D <sub>1</sub>	4 mm
$\varnothing$ D <sub>2</sub>	9 mm
External $\varnothing$ D	25 mm
Adapter	SK 50 A = 160
Arbor standard	ISO 7388-1
Shape	ADB

Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Shrink-fit chuck

## Accessories

Pull stud 90° sealed suitable for steep tapers 50	308795 50
Shrink-fit chuck extension 4.5° without length adjustment screw Ø d / Ø D1 16/4 mm	302410 16/4
Pull stud Form B suitable for steep tapers 50	308640 50
Pull stud 45° sealed suitable for steep tapers 50	308760 50
Pull stud sealed, form B suitable for steep tapers 50	308650 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Pull stud sealed, form B suitable for steep tapers 50	308620 50
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50	308820 50
Pull stud stud sealed, form A suitable for steep tapers 50	308610 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
Cooling unit Type CU1	354215 CU1
Pull stud Form A suitable for steep tapers 50	308600 50
Shrink-fit chuck extension 4.5° without length adjustment screw Ø d / Ø D1 12/4 mm	302410 12/4
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Special pull stud with internal thread suitable for steep tapers 50	308740 50
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
	308700 50

Special pull stud with no internal thread sealed suitable for steep tapers 50

Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50	308605 50
Pull stud 45° sealed suitable for steep tapers 50	308765 50
Pull stud sealed suitable for steep tapers 50	308660 50
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50	308812 50
Basic tool mounting for SK for SK taper shank 50 SK	354225 50
Shrink-fit unit Type SU1	354210 SU1