

**Garant**
**SK shrink-fit chucks 3°, SK 40 A = 80, Clamping range Ø D1: 12 mm**

**Order data**

Order number	302352 12
GTIN	4045197480033
Item class	31A

**Description**
**Version:**

- All shanks hard turned (for smooth running!).
- With Balluffchip bore.
- Extra slim design (3° contour).

**Application:**

- Especially for tool and mould making.
- Wherever reduced interference contours are required.
- For clamping tools with shank tolerance h6.

**Optional extras:**

Pull studs (PS) No. 308600 – 308806. PS wrenches No. 308820 – 308835. Shrink-fit chuck extensions No. 302410 size 12/3 and 12/4. Shrink-fitting units No. 354210 – 304450.

**Note:**

No length adjustment available!

Machining strategy: HSC

External Ø D: 25 mm

Ø D<sub>2</sub>: 18 mm

**Technical description**

Ø D <sub>2</sub>	18 mm
Clamping Ø D <sub>1</sub>	12 mm
External Ø D	25 mm
Adapter	SK 40 A = 80

Arbor standard	DIN 69871
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Shrink-fit chuck

## Accessories

Screening plate for coil SU1 for clamping Ø 6-12 mm	354240 6-12
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Screening plate for coil SU1 for clamping Ø 12-20 mm	354240 12-20
Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Wrench for pull studs ISO 7388 suitable for steep tapers 40 SK	308830 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Shrink-fit unit Type SU1	354210 SU1
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for steep tapers 40 SK	308820 40
Cooling adapter short 4.5° for clamping Ø 9,1-12 mm	354235 9,1-12
Cooling adapter long 4.5° for clamping Ø 9,1-12 mm	354236 9,1-12

Pull stud Form B suitable for steep tapers 40	308640 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Pull stud sealed suitable for steep tapers 40	308635 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull stud sealed, form B suitable for steep tapers 40	308650 40
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud Form A suitable for steep tapers 40	308600 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Cooling unit Type CU1	354215 CU1
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Torque insert for Pull studs to DIN 69872 suitable for steep tapers 40 SK	308810 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Torque insert for Pull studs to SO 7388 suitable for steep tapers 40 SK	308812 40
Basic tool mounting for SK for taper shank 40 SK	354225 40
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40