



Side lock arbor, SK 40, Clamping range \varnothing D1: 12 mm



Order data

Order number	302420 12
GTIN	4250122600251
Item class	36E

Description

Version:

Internal thread for manual clamping.

Application:

For clamping tools with side flat to DIN 1835 B and DIN 6535 HB.

Concentricity: $\leq 3 \mu\text{m}$

Overhang dimension A: 50 mm

External \varnothing D: 42 mm

Overall length L: 143 mm

Thread M: M16

Spare clamping screw No. 30 9900: 12

Technical description

Spare clamping screw No. 30 9900	12
Overall length L	143 mm
Overhang dimension A	50 mm
Thread M	M16
Clamping \varnothing D ₁	12 mm
External \varnothing D	42 mm
Adapter	SK 40
Standard	DIN 6359

Arbor standard	DIN 2080
Concentricity	≤ 3 μm
Type of product	Side lock arbor

Accessories

Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud Form A suitable for steep tapers 40	308600 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Pull stud sealed suitable for steep tapers 40	308660 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
	308802 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40

Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40 308605 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40 308630 40

Pull stud sealed suitable for steep tapers 40 308635 40

Special pull stud with internal thread suitable for steep tapers 40 308740 40

Pull stud 90° sealed suitable for steep tapers 40 308790 40

Pull stud sealed, form B suitable for steep tapers 40 308650 40

Pull stud Form B suitable for steep tapers 40 308640 40

Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40 308810 40

Pull stud sealed, form B suitable for steep tapers 40 308620 40

Pull stud 45° sealed suitable for steep tapers 40 308760 40

Pull stud 45° sealed suitable for steep tapers 40 308765 40

Spare clamping screw for chucks with clamping \varnothing D1 12 mm 309900 12