



Side lock arbor, SK 50, Clamping range \varnothing D1: 12 mm



Order data

Order number	302440 12
GTIN	4250122600367
Item class	36E

Description

Version:

Internal thread for manual clamping.

Application:

For clamping tools with side flat to DIN 1835 B and DIN 6535 HB.

Concentricity: $\leq 3 \mu\text{m}$

Overhang dimension A: 63 mm

External \varnothing D: 42 mm

Overall length L: 190 mm

Thread M: M24

Spare clamping screw No. 30 9900: 12

Technical description

Thread M	M24
Spare clamping screw No. 30 9900	12
Overhang dimension A	63 mm
Overall length L	190 mm
Clamping \varnothing D ₁	12 mm
External \varnothing D	42 mm
Adapter	SK 50

Standard	DIN 6359
Arbor standard	DIN 2080
Concentricity	≤ 3 µm
Type of product	Side lock arbor

Accessories

Pull stud 45° sealed suitable for steep tapers 50	308760 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
Pull stud sealed, form A suitable for steep tapers 50	308610 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308700 50
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50	308820 50
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50	308605 50
Pull stud sealed, form B suitable for steep tapers 50	308650 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
Special pull stud with internal thread suitable for steep tapers 50	308740 50
Pull stud sealed suitable for steep tapers 50	308660 50
Pull stud 45° sealed suitable for steep tapers 50	308765 50
Pull-stud 60° sealed suitable for steep tapers 50	308780 50
Pull stud Form B suitable for steep tapers 50	308640 50
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50	308812 50
	308830 50

Wrench for pull studs ISO 7388 suitable for ISO taper size 50

Pull stud Form A suitable for steep tapers 50	308600 50
Pull stud sealed, form B suitable for steep tapers 50	308620 50
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Spare clamping screw for chucks with clamping \varnothing D1 12 mm	309900 12