



Short drill chuck Form A, SK 40, Clamping range: 1-13 mm



Order data

Order number	302540 1-13
GTIN	4045197307668
Item class	37D

Description

Version:

For clockwise and anticlockwise rotation. Internal thread for manual clamping.

Application:

For clamping drills, countersinks, and reamers on milling machines.

Supplied with:

Hexagon screwdriver with T-handle.

maximum tightening torque $M_{d\max} \leq 14 \text{ Nm}$

Overhang dimension A: 80 mm

External \varnothing D: 43 mm

Spare chuck key No. 627425: SW6

Technical description

Spare chuck key No. 627425	SW6
Clamping range	1 - 13 mm
Overhang dimension A	80 mm
External \varnothing D	43 mm
Adapter	SK 40
Arbor standard	DIN 2080
Shape	A
maximum tightening torque $M_{d\max}$	$\leq 14 \text{ Nm}$

Type of product	Short drill chuck
-----------------	-------------------

Accessories

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Pull stud Form B suitable for steep tapers 40	308640 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud sealed suitable for steep tapers 40	308635 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull stud Form A suitable for steep tapers 40	308600 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Hexagon screwdriver, with T-handle Hexagon 6 mm	627481 6

Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Hexagon screwdriver with T-handle Hexagon 6 mm	627425 6
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Pull stud sealed, form B suitable for steep tapers 40	308650 40
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40